# **AIR SUPPLY SYSTEM** AIR BOTTLES, TROLLEYS AND ACCESSORIES

### **AIR BOTTLE CONNECTORS**

2		3 []-[1]			4 NUAL
	1 Air bottle	3	Air bottle conne	ctor	Operating and
$\sum$	2 Air bottle ho	ose 4	Air pressure reg	ulator	Maintenance Manual
	CODE	WORKING PRESSURE	DESCRIPTION	UNI CODE (OLD)	UNI CODE (NEW)
	B.01.0001	220 bar	COD-BSP		BS341 NR3
	B.01.0002	220 bar	COD-D		DIN 477-13
	B.01.0029	220 bar	COD-D		DIN 477-13
	B.01.0003	220 bar	COD-FR-J	ex UNI 4406 02	UNI 11144 NR2
B.01.0006	B.01.0004	220 bar	COD-FR-N2		NF E29-650
	B.01.0005	220 bar	COD-IT	ex UNI 4410 AIR	UNI 11144 NR6
innin	B.01.0006	220 bar	COD-N2	ex UNI 4409 N2	UNI 11144 NR5
	B.01.0007	220 bar	COD-US	ex UNI 4412 AR-HE	UNI 11144 NR8
B.01.0007	B.01.0011	220 bar	COD-J	JAPAN	
	B.01.0014	220 bar	COD-IN	INDIAN STANDARD	3224 2002
	B.01.0013	220 bar	COD-CN	CHINA	N2 G5/8"
	B.01.0016	220 bar	CGA580	use with F1, F2, F9 2.	0
	B.01.0017	220 bar	CGA580	use with F6, F7	
B.01.0017	B.01.0027	300 bar	DIN 300	with pin	

# BOTTLE CONNECTION SUPPORT

B.01.0002


B.01.0011

B.01.0013



This support connects the air bottle connector to the air pressure regulator. Suitable for F1 and F2 air pressure regulators.

Technical Data: Thread IN: 1/4" BSP female Thread OUT: 3/8" BSP male



**ADAPTERS** 




#### B.40.0056

#### NEW ADAPTER FOR PRESSURE REGULATORS

New adapter for air pressure regulators F40 and F15.

Technical Data: Thread IN: 1/4" BSP female Thread OUT: M15x1 male



## **AIR BOTTLE COVERS**



#### AIR BOTTLE COVER FOR PAOLI AIR BOTTLES

- Black textile cover
- Available for 18 and 15 litres air bottles
- New design

PRODUCT CODE	LITRES
B.22.05.0000	18
B.22.05.0001	15



### **AIR BOTTLE**



#### COMPOSITE AIR BOTTLE WITH CARBON FIBER

- Capacity: 9 liters
- Max pressure at 15° C: 300 bar
- Double connection (B.22.01.0014)

Air bottle valves M25x2: Double connection (B.22.04.0011)





**DOUBLE INLET BOTTLE** 

B.22.01.0003 B.22.01.0001



MOBILE AIR BOTTLE

Ideal to restore the tire pressure. Equipped with: pressure gauge, air pressure regulator, hooking system on the belt.

212210110002		Tyre inflating gun not included		
PRODUCT CODE	CAPACITY (LITRES)	PRESSURE (BAR)	CONNECTION	CONNECTION TYPE
B.22.01.0000	15	200	Single	INT - Female / DIN - Male
B.22.01.0003*	15	200	Double	INT - Female / DIN - Male
B.22.01.0002**	18	220	Single	INT - Female / DIN - Male
B.22.01.0001*/**	18	220	Double	INT - Female / DIN - Male
C.01.0009	1	200		

\* Suggested in order to avoid to dismount the air pressure regulator while recharging the bottle \*\* Just on demand

## **AIR BOTTLE TROLLEYS**



C.01.0002 Double

- Just one trolley capable to carry the 15 or the 18 litres bottles.
- The trolley has got a support specifically designed for the PAOLI PIT STOP<sup>®</sup> Regulators F1, F2.
- Two brackets designed to roll and easily carry the supply hose.

#### AIR BOTTLE TROLLEY KIT INCLUDED



Accessories included: belt, fixing nut and high pressure hose to connect the air bottle to the air pressure regulator.

PRODUCT CODE	OVERALL DIMENSIONS	WEIGHT (W/O BOTTLE AND REGULATOR)	WEIGHT (WITH BOTTLE AND REGULATOR)
C.01.0003	47,3 x 39,5 x 116 cm	10,1 kg	36,6 kg
C.01.0002	47,3 x 65 x 116 cm	18 kg	71 kg

The double trolley can

be converted in single

trolley



### **DOUBLE TROLLEY KIT**

EXTRA-STRONG MICROPALLINATED STAINLESS STEEL CHASSIS

#### DOUBLE CONNECTION BOTTLES FOR EASY FILLING

#### HIGH PRESSURE HOSE TO CONNECT – THE AIR BOTTLE TO THE AIR PRESSURE REGULATOR.

C.01.0011

The kit includes:

- No. 1 double trolley
- No. 2 18 litres bottles with double connection
- No. 2 air bottle trolley kit
- No. 1 F5 air pressure regulator (DIN air bottle connector included)

Also available with 2 F5 air pressure regulators (code C.01.0013).




## SINGLE TROLLEY KIT






### **MINI TROLLEY KIT**







The air bottle valve is available with single or double connection. It can be fitted with the connection placed upon the air bottle collar M25x2.



# **BOTTLE ANTI-DEFLAGRATION BOOTHS**



#### WORK SAFELY!

NEV

New anti-deflagration cabins allows you to safely recharge two or four cylinders at a time, protecting you and your working environment from debris caused by any air expansion explosion.

PRODUCT CODE	PRODUCT	NET WEIGHT	FITTINGS	TANK STORAGE B x W x H
B.22.07.0000	2 CYLINDERS CABIN	222 kg 452 lb	DIN 300 bar	60 x 73 x 104 cm 23.6 x 28.7 x40.9 in
B.22.07.0001	4 CYLINDERS CABIN	500 kg 1102 lb	DIN 300 bar	70 x 65 x 80 x 116 (H2) cm 27.5 x 25.6 x 31.5 x 45.6 (H2) in

# EXTRA FLOW SAFETY VALVE



An additional safety system designed to intervene in the event that the valve breaks, for example in the case of an accidental fall. In case the valve is damaged, the outflow pushes the sphere, held in the rest position by the calibrated spring, until the partial closure of the dipstick, a micro-hole still allows the discharge of the air counted in the cylinder with a reduced flow.

PRODUCT CODE	DESCRIPTION	INLET
B.22.08.0000	EXTRA FLOW SAFETY VALVE M6X0,75	M6
B.22.08.0001	EXTRA FLOW SAFETY VALVE M8X0,75	M8

